

CSR1300A

DEACRO
LEADERS IN INNOVATIVE ENGINEERING

"THE CSR1300A REDEFINES EXCELLENCE IN CENTER SURFACE SLITTER REWINDER TECHNOLOGY"

CSR50A OVERVIEW

The CSR1300A simplex center-surface slitter rewinder is the most technologically advanced and versatile simplex slitter in the industry. Center-surface winding is ideal when rewinding to large ODs (up to 50"/1300 mm) for heavy materials such as papers and complex laminates. Winding directly off of a drum provides good tracking to virtually eliminate web interweaving.

At the touch of a button, the slitter can be set to the correct running parameters. Digital knife positioning and servo laser core indication options can greatly reduce setup times. When rewinding is complete, rewind arms hydraulically rotate out of the machine to an unloading position. A setup change is as simple as recalling a new file through the color touch screen.

When the rewinding is complete, the slitter can automatically off-load the finished rolls to one of many different roll handling options. The operator then simply slides new cores on and continues the cycle. A set change is as simple as recalling a new file through the color touch screen. Operators never need to handle rewind tooling, handle shafts, setup knives or manually move rolls!

FEATURES & OPTIONS

- Rewind up to 50" OD (1300 mm) rolls
- Center-surface virtually eliminates web interweaving
- Ideal for heavy gauge/high tension materials
- Servo laser core indication
- Automatic knife positioning
- Digital knife positioning
- Touch control screen interface
- Database file management for repeatability
- Closed loop unwind tension control
- Splice table & pneumatic web clamping
- Shaft handling systems available



MACHINE SPECIFICATIONS

Rewind Roll Dia.	50"	1300 mm
Unwind Roll Dia.	40/50"	1000/1300 mm
Max. Web Width	63" +	1600 mm +
Max. Web Speed	1500/2000 fpm	450/600 mpm